


## 3-Way Sanitary Clamp End Direct Mount Ball Valve





- ASTM A351 CF8M 316 Stainless Steel construction, 316 Trim.
- Virgin PTFE Seals and Cavity Filled Ball Seats. L-Port and T-Port configurations. Full Bore.
- ISO 5211 Direct Mounting Pad and Square Stem for easy automation.
- Lockable Lever. Mirror Polished Bore. BS4825 Clamp End connections.
- Valves are Full Bore and are therefore suitable for use on Piggled pipework.

**100mm high Spindle Extension for Insulation & Actuation Heating Jacket can be fitted to base of valve only. DIN 11851, SMS, IDF and RJT Ends can also be supplied on short lead times.**

**Available size range: 1/2" - 3"**

Item	Part	Material	Qty.
1	Body	A351-CF8M	1
2	Cap	A351-CF8M	4
3	Ball	A351-CF8M	1
4	Seat	PTFE	4
5	Gasket	PTFE	2
6	Thrust Washer	PTFE	1
7	O-Ring	FKM	1
8	Stem Packing	PTFE	1
9	Ring	AISI 304	1
10	Bellville Washer	AISI 301	2
11	Stop Pin	AISI 316	1
12	Nut	AISI 304	1
13	Stem	AISI 316	1
14	Handle	AISI 304	1
15	Spring Washer	AISI 304	16
16	Bolt	AISI 304	16
17	Washer	AISI 304	1
18	Nut	AISI 304	1



SIZE	DN	ISO5211	W	H	H1	C	R	L	L1	øD	ød	Torque/ INLB
1/2"	15	F03/F04	121	78	44.5	9	9	118	20	12.7	9.5	85
3/4"	20	F03/F04	121	82	48	9	9	127	20	19.1	15.8	90
1"	25	F04/F05	137	90	59	11	11	152.4	25	25.4	22.2	150
1-1/2"	40	F05/F07	182	110	72	14	14	175	25	38.2	35	350
2"	50	F05/F07	182	114.7	82	14	14	190	25	50.8	47.6	780
2-1/2"	65	F07/F10	370	105.5	97.5	17	17	228	25	77.5	60.2	1085
3"	80	F10/F12	400	129	120.5	23	22	260.6	25	90.9	73	1597