


2-Pce Screwed Full Bore Ball Valve lever operated



- ASTM A351 CF8M 316 Stainless Steel construction, 316 Trim. PTFE Seats and Seals. Adjustable gland. Slide type Locking Lever. 1000 psi/g Pressure rated.
- -20 / + 180 Deg C Temperature rated.
- Pressure balance hole in Ball Slot.
- BSP Screwed end connections.
- CE marked (sizes 1.1/4" upward) in accordance with the PED 2014/68/EU.


A good quality, general purpose ball valve suitable for most Liquid and Gaseous duties. Ball can be drilled for upstream vent applications such as bleach and peroxide duties.

Full material Test Certificates available

Test standard – API 598

BSP Ends - ISO 7-1 (Female)

Available size range: 1/4" - 4"



Item	Part	Material	Qty.
1	Handle Cover	PLASTIC	1
2	Body	CF8M	1
3	Ball Seat	PTFE	2
4	Ball	CF8M	1
5	Cap	CF8M	1
6	Thrust Washer	PTFE	1
7	Stem Packing	PTFE	1
8	Gland Nut	304	1
9	Spring Washer	304	1
10	Stem Nut	304	1
11	Stem	316	1
12	Locking Device	304	1
13	Handle	304	1

SIZE	d	L	H	W
1/4"	9.2	54	49	98
3/8"	12.8	54	50	98
1/2"	15	57	50	100
3/4"	20	68	53	100
1"	25	80	68.5	128
1-1/4"	32	91	72.5	128
1-1/2"	38	103	81	143
2"	50	124	99	143
2-1/2"	65	160	119	222
3"	80	185	132	222
4"	100	207	180	335