


Y-Type Strainer Flanged BS4504 DIN PN16



- ASTM A351 CF8M 316 Stainless Steel Body and Cover.
- PTFE Cover Seal. 316 Stainless Steel Filter Element.
- 316 Stainless Steel Drain Plug in Cover. Bolted Cover design.
- Face to Face dimension in accordance with DIN 3202/F1.
- 16 bar pressure rated.
- -20 / +200 deg C Temp rated.
- Flanged PN16 end connections.
- CE marked in accordance with PED 2014/68/EU (from 1.1/4").
- Element std perf 1.5mm (1/2" - 1") & 2mm (1.1/4" - 10").

Test Standard API 598.

Available size range: 1/2" - 10

Item	Part	Material	Qty.
1	Body	CF8M	1
2	Screen	SUS316	1
3	Gasket	PTFE	1
4	Bonnet	CF8M	1
5	Gasket	PTFE	1
6	Stopper	CF8M	1
7	Spring Washers	SUS304	1
8	Bonnet Bolt	A4-70	1

SIZE	d	L	H	D	C	G	f	T	N-ØM
1/2"	15	130	85	95	65	45	2	14	4-Ø14
3/4"	20	150	87	105	75	58	2	16	4-Ø14
1"	25	160	114	115	85	68	2	16	4-Ø14
1-1/4"	32	180	114	140	100	78	2	16	4-Ø18
1-1/2"	40	200	135	150	110	88	3	16	4-Ø18
2"	50	230	155	165	125	102	3	18	4-Ø18
2-1/2"	65	290	189	185	145	122	3	20	4-Ø18
3"	80	310	200	200	160	138	3	20	8-Ø18
4"	100	350	232	220	180	158	3	20	8-Ø18
5"	125	400	274	250	210	188	3	22	8-Ø18
6"	150	480	326	285	240	212	3	22	8-Ø22
8"	200	600	397	340	295	268	3	24	12-Ø22
10"	250	730	512	405	355	320	3	26	12-Ø26

