

2-Pce Full Bore Venting Ball Valve



- ASTM A351 CF8M 316 Stainless Steel construction
- PTFE Ball Seats and Seals. BSP Screwed end connections.
- Slide Type Lockable Lever.
- 2mm Venting Hole in Ball and Valve Body to safely vent downstream pressure to atmosphere when the valve is in the closed position.


This valve is designed primarily (but not exclusively) for use as a "Safety Feature" on Compressed Air (or other non-hazardous gas) Pipework Systems.

More commonly found available in Nickel Plated Brass, the valve is used to vent downstream line pressure through the base of the valve body to atmosphere.


BSP Ends - BSPP ISO 228/1

Available size range: 1/4" - 2"

SIZE	ød	L	H	W	E	G	HEX.B
1/4"	10.6	58	58	100	12.7	28.5	23.5
3/8"	12	58	58	100	12.7	28.5	23.5
1/2"	15	62	58	100	12.7	28.5	25
3/4"	20	72.4	64	129	22	34.8	32
1"	25	85	77	156	22	34.8	41
1-1/4"	32	94	83	156	23.6	38.1	50
1-1/2"	38	105	96	182.5	23.6	38.1	56
2"	50	125	102	182.5	23.6	38.1	70



Item	Part	Material	Qty.
1	Body	CF8M	1
2	End Cap	CF8M	1
3	Ball	CF8M	1
4	Body Seat	PTFE	1
5	Stem	SUS316	1
6	Body Gasket	PTFE	1
7	Thrust Washer	PTFE	1
8	V-Ring Packing	PTFE	1
9	Gland Nut	SUS304	1
10	Stem Nut	A194-B	1
11	Locking Device	SUS304	1
12	Handle Sleeve	VINYL PLASTIC	1
13	Handle	SUS304	1
14	Locking Device	SUS304	1



Pressure-Temp. Rating

