




Screwed Pattern Globe Valve



- ASTM A351 CF8M 316 Stainless Steel Body, Bonnet and Disc.
- 316 Stainless Steel Stem and Trim. Ductile Iron painted Handwheel.
- PTFE Gland Packing and Bonnet Seal.
- Screwed Bonnet. Non Rising Stem. Metal to Metal Taper Seat.
- 600 psi/g pressure rated.
- -20 / +180 deg C Temp rated.
- BSP screwed end connections to ISO 7/1 Rp (sizes 1/4" - 2") and NPT to ASME B1.20.1 (sizes 1/2" - 2").
- CE marked in accordance with the PED 2014/68/EU (from 1.1/4").

Item	Part	Material	Qty.
1	Body	CF8M	1
2	Seat	SS316	1
3	Stem	SS316	1
4	Cap	CF8M	1
5	Gasket	PTFE	1
6	Washer	SS304	1
7	Stem Packing	PTFE	1
8	Ring	SS304	1
9	Gland Ring	SS304	1
10	Handwheel Nut	SS304	1
11	Plate	SS304	1
12	Hand Wheel	CAST IRON	1

A good all round, robust general purpose Globe Valve used for both isolation and flow restriction duties. The 600 psi pressure rating is relatively unique as most companies are only able to offer a 200 psi unit. We are able to machine the valve ends to Socket Weld as an optional extra.

Available size range: 1/4" - 2"

SIZE	d	L	H	A	Kgs
1/4"	10	67	79	65	0.5
3/8"	12	67	79	65	0.5
1/2"	15	67	79	65	0.48
3/4"	20	80	91	77	0.68
1"	25	89	106	77	0.96
1-1/4"	32	100	125	97	1.56
1-1/2"	40	118	136	97	2.20
2"	50	134	146	97	2.88

Pressure-Temp. Rating

