



Features:

1. Working Pressure: 1/2"-2" 1000psi
2. Temperature Range: -20 to 180 °C
3. Full Port
4. Investment Casting
5. Blow-out Proof Stem
6. Locking Device Handle (Option)
7. PED 2014/68/EU
8. Casting Approved AD2000-WO
9. Inspection Testing: API598, EN12266-1
10. Design Standard BS4825

Size	A	B	C	D	E	F	L	H	W
1/2"	25.4	20.3	12.7	9.4	1.6	3.7	85.3	56.5	108.5
3/4"	25.4	20.3	19.05	15.75	1.6	3.7	90	62.2	108.5
1"	50.5	43.5	25.4	22.1	1.6	2.85	114	70.5	130.5
1-1/2"	50.5	43.5	38.1	34.8	1.6	2.85	138	92	162.5
2"	64	56.5	50.8	47.4	1.6	2.85	158	101	162.5

17	HANDLE	304	1
16	LOCK DEVICE	304	1
15	STEM PACKING	PTFE	1
14	BALL SEAT	PTFE	2
13	BALL	316	1
12	BODY	CF8M	1
11	END CAP	CF3M	2
10	BOLT NUT	304	4
9	BOLT WASHER	304	4
8	BOLT	304	4
7	SEAL	PTFE	2
6	THRUST WASHER	PTFE	1
5	GLAND NUT	304	1
4	SPRING WASHER	304	1
3	STEM NUT	304	1
2	STEM	316	1
1	HAND SLEEVE	PLASTIC	1
NO.	NAME	MATERIAL	Q' TY
	3PC Clamp Sanitary Cavity Filled Ball Valve		
	ETG SJG-80C		

**G.C. SUPPLIES UK LTD**  
**TEL:+44 (0) 161-681-8114**  
**FAX:+44 (0) 161-947-0148**