


DN	SIZE	d	D	L	Kgs
DN8	1/4"	8	30.5	53	0.17
DN10	3/8"	10	30.5	53	0.15
DN15	1/2"	15	37	56	0.21
DN20	3/4"	20	42	63	0.29
DN25	1"	25	48	74	0.40
DN32	1-1/4"	30	58	81	0.65
DN40	1-1/2"	38	70	91	0.98
DN50	2"	47	82	97	1.40
DN65	2-1/2"	61	102.5	118	2.44
DN80	3"	75	120	138	3.80
DN100	4"	94	150	158	6.60



ITEM	PART	MATERIAL	QTY.
01	Cap	CF8M	1
02	Body Gasket	PPL	1
03	Disc	CF8M	1
04	Body	CF8M	1
05	Spring	SS316	1

Tech. data:

- 1.Designandinspectioncode: EN12516-1/-2, EN12266-1;
- 2.The main material: according to PED97/23/EC Annex1, Par.4.3and3.1 certificates;
- 3.Design pressure: 1000PSI(PN63);
- 4.Working temperature: -25°C ~ +180°C;
- 5.Applicable fluid: water, gas, oil;
- 6.Thread Ends: ANSI B2.1, BS21, DIN259/2999;
- 7.Pressure Test: EN12266-1, API598;
- 8.€ marking only for the size DN32~ DN100;
- 9.Making: see marking drawing.

				MATERIAL	CF8M	G.C. SUPPLIES UK LIMITED	
				QUANTITY			
				SCALE			
				WEIGHT			
					SUPPLY STATUS	PART NAME	
MARK	REVISED		SIGN	DATE:			
DESIGNED	高亚忠	2014. 01. 22	REVIEWED	宗城辉			
APPROVED	宗城辉	2014. 01. 22	DATE:	2014. 01. 22	PAGE1 OF 1	ETG SPV-69S	