



| SIZE | L | H | W | E | F |
|--------|-----|-------|-------|-------|-------|
| 1/2" | 90 | 56.5 | 108.5 | 9.5 | 12.7 |
| 3/4" | 90 | 62.3 | 108.5 | 15.85 | 19.05 |
| 1" | 100 | 70.5 | 130.5 | 22.2 | 25.4 |
| 1 1/2" | 125 | 92 | 162.5 | 34.9 | 38.1 |
| 2" | 150 | 101 | 162.5 | 47.6 | 50.8 |
| 2 1/2" | 190 | 129.5 | 247 | 60.3 | 63.5 |
| 3" | 220 | 138.5 | 247 | 73 | 76.2 |

3PC Butt-Weld Sanitary Cavity Filled Ball Valve Features:

1. Pressure Rating: 1000PSI from DN25 to DN50 and 400PSI for DN80
2. Working Temperature: -20° C to +180° C
3. Full Port
4. Investment Casting
5. Blow-out Proof Stem
6. Locking Device Handle
7. PED 2014/68/EU
8. Inspection Testing: API598, EN12266-1

| 17 | HANDLE | 304 | 1 |
|-----|---------------|----------|-------|
| 16 | LOCK DEVICE | 304 | 1 |
| 15 | STEM PACKING | PTFE | 1 |
| 14 | BALL SEAT | PTFE | 2 |
| 13 | BALL | 316 | 1 |
| 12 | BODY | 316 | 1 |
| 11 | END CAP | 316L | 2 |
| 10 | BOLT NUT | 304 | 4 |
| 9 | BOLT WASHER | 304 | 4 |
| 8 | BOLT | 304 | 4 |
| 7 | SEAL | PTFE | 2 |
| 6 | THRUST WASHER | PTFE | 1 |
| 5 | GLAND NUT | 304 | 1 |
| 4 | SPRING WASHER | 304 | 1 |
| 3 | STEM NUT | 304 | 1 |
| 2 | STEM | 316 | 1 |
| 1 | HAND SLEEVE | PLASTIC | 1 |
| NO. | NAME | MATERIAL | Q' TY |

| 制图 | 审核 | 材质 | 比例 | 备注 |
|------------|---|----|----|----|
| | | | | |
| 产品名称 | 3PC Butt-Weld Sanitary Cavity Filled Ball Valve | | | |
| ETG SJG-80 | | | | |